

Manual Spray Gun W 400



Gravity



CERTIFICATE OF COMPLIANCE

We certify that we have tested the Anest Iwata High T.E.C. W 400 gravity spray gun in accordance with ASTM Designation: D5286-95 Tests for transfer efficiency and that this spray gun complies with the requirements of the Environmental Protection Act 1990, Part I - 1997 Revision as detailed in PG6/34(97), PG6/23(97), PG6/40(94), PG6/41(94).

TWO COAT SYSTEM		THREE COAT SYSTEM	
PRIMER	92.0%	PRIMER	92.0%
SOLID COLOUR	76.9%	BASECOAT	76.4%
SYSTEM	84.5%	CLEARCOAT SYSTEM	81.0%

Signed for MIRRRC THATCHAM: M. Smith
Chief Executive

THATCHAM
THE MOTOR INSURANCE
REPAIR RESEARCH CENTRE
Colthrop Way, Thatcham, Berkshire, RG19 4NR U.K.

CE Ex II 2 G X



TECHNICAL SPECIFICATIONS

Model	Ø mm	bar	NI/min	ml/min	mm	No.	g
W400 - 082 G	0.8	2.0	280	60	80	LV2	380 only gun
W400 - 102 G	1.0			95	150		
W400 - 122 G	1.2			140	175		
W400 - 132 G	1.3			160	225		
W400 - 142 G	1.4			210	225		
W400 - 152 G	1.5			230	250		
W400 - 162 G	1.6			240	270		
W400 - 182 G	1.8	290	320	260	LV1		
W400 - 202 G	2.0	3.0	360	460	320	R 2	
W400 - 251 G	2.5	360	580	340	W1		

Max. Working Pressure: 6.8 bar Noise Level (L_{AeqT}): 79.7 dB (A)
 Temperature range: 5~40° C Air Nipple G 1/4" Fluid Nipple (gravity) M16 x1.5mm

Distributed by: